

Deadbreak Cable Adapters

Product Data Sheet

Deadbreak Cable Adapters are used to adapt a multitude of medium voltage cable sizes to a standard housing size. The cable adapter is installed onto the prepared cable and the associated housing (Deadbreak Elbow or Disconnectable Joint Sleeve) is pushed over the cable adapter. The adapters are designed to maintain an interference fit with the inside diameter of the cable entrance of the housing. Care must be taken when selecting the Cable Adapter size to ensure the adapter maintains an interference fit with the cable insulation system. There are two types are cable adapters which are explained in this Product Data Sheet. Be sure to select the appropriate Cable Adapter for the associated housing.

Features

- Injection Molded from EPDM
- Peroxide-Cured
- Complete with Ergonomic Assembly Aid Wedge
- Made in the USA

Cable Range

Size	in	mm
E	0.530 - 0.675	12.57 - 17.15
F	0.640 - 0.820	16.26 - 20.83
G	0.760 - 0.950	19.30 - 24.13
H	0.850 - 1.050	21.59 - 26.67
J	0.980 - 1.180	24.86 - 29.92
K	1.090 - 1.310	27.69 - 33.27
L	1.180 - 1.465	29.97 - 37.21
LM	1.280 - 1.430	32.51 - 36.32
M	1.370 - 1.630	34.80 - 41.40
MN	1.480 - 1.700	37.59 - 43.18
N	1.515 - 1.780	38.48 - 45.21
PA	1.665 - 1.785	42.29 - 45.34
P	1.725 - 1.935	43.82 - 49.15
PQ	1.795 - 1.935	45.59 - 49.15

P625CA Cable Adapters are designed for use with:

- 15/25kV Deadbreak Elbows
- 15/25 & 35kV Disconnectable Joints

P625CA



Cable Range

Size	in	mm
H	0.850 - 1.050	21.59 - 26.67
J	0.980 - 1.180	24.86 - 29.92
K	1.090 - 1.310	27.69 - 33.27
L	1.180 - 1.465	29.97 - 37.21
LM	1.280 - 1.480	32.51 - 37.59
M	1.370 - 1.630	34.80 - 41.40
MN	1.480 - 1.700	37.59 - 43.18
N	1.515 - 1.780	38.48 - 45.21
P	1.725 - 1.935	43.82 - 49.15
Q	1.900 - 2.230	48.23 - 56.64

P635CA Cable Adapters are designed for use with:

- 35kV Deadbreak Elbows

P635CA

